

## Longspan Shelving Trolley

Super-strong end frames supplied pre-built  
 Quick & easy assembly  
 Z profile steel shelf support beams  
 18mm thick high density chipboard shelves  
 Shelves are adjustable every 2" (50mm)  
 3 levels as standard

### Size Options

Heights: 2000, 2500mm  
 Widths: 950, 1500, 1800, 2250, 2400mm  
 Depths: 600, 900, 1200mm

### Safety Information:

Total Trolley Capacity: up to **400kg (UDL)**

The above capacity is based upon the standard 3 shelf model (shown). Each extra level added, reduces the overall capacity of the trolley by 50kg.

### Safety Notes:

These trolleys are designed for use on smooth floor surfaces in warehouse environments. In situations where the ground is uneven, we recommend that the trolley should be used at below 50% of the overall capacity.

Trolleys should be loaded with the heaviest items placed on the lower shelves. Although each shelf is capable of holding up to 400kg in weight, the trolley capacity and the requirement of a uniformly distributed load restricts the usable shelf load to a lower value.

### Recommended shelf loadings (2m high trolley with 3 shelves):

Top Shelf = Do not exceed 25kg  
 Middle Shelf = Do not exceed 100kg  
 Bottom Shelf = Do not exceed 225kg  
 Total: 350kg (50kg under maximum trolley capacity)

The above example is for guidance only, if in doubt please contact EZR Shelving for advice.



**Note:** For overall width add 120mm to the nominal shelf width



E-Z-Rect Ltd, Unit 8c Witan Park, Avenue Two, Station Lane, Witney, Oxon, OX28 4FH